

IWTRHT

AMBIENT TEMPERATURE & RH WIRELESS TRANSMITTER



The IWTRhT ambient temperature and relative humidity transmitter has been designed to operate with the range of wireless receivers designed and manufactured by Sensata.

Either ambient temperature alone or both temperature and humidity measurements can be specified. (see IWTT)

Typically the unit transmits the measured values back to a IWR-PORT which can be connected to an Ethernet or RS232/485 communications network.

The unit is specially designed to maximize battery life and in a typical application the battery life can exceed three years.

Two mounting head styles are available, an industrial wall or ceiling mounting unit or a commercial style version.

Accessories include a DIN rail mounting clip and cap retaining strap.

Features

- Measures ambient temperature and relative humidity
- High accuracy
- Long battery life
- User selectable update rates
- Based on IEC 802.15 protocol

SPECIFICATIONS

Technical

Parameter	Min	Typ	Max	Comments
Supply Voltage		3.6V		Battery powered
Supply Current (mA)			40	When transmitting data
Battery Life		100kΩ		Dependent on upgrade rate
Ambient Temperature Range	-40°C		80°C	
Relative Humidity Range	0%		100%	
Temperature Accuracy		±0.5°C		At 30°C
Relative Humidity Accuracy		±3%		Between 10 and 90% RH

Enclosure Styles

Style	Industrial Head
Orientation	Any
Wall/Ceiling Mounting	2 x 3mm screws
Enclosure Size	85mm dia x 57mm deep
Weight	Approx 70g



ORDERING OPTIONS

Example : IWTRhT

Please supply

Part Number: IWTRhT

Five Channel Configuration Software*: IWR-Set

*Download free user configuration software here:

https://www.cynergy3.com/sites/default/files/IWR-Set_v2.4_installer.zip

Made in the UK

Page 2

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

CONTACT US

+44 (0)1202 897969
c3w_sales@sensata.com
Cynergy3 Components Ltd.
7 Cobham Road,
Ferndown Industrial Estate,
Wimborne, Dorset,
BH21 7PE, United Kingdom