

## 4BTD2-24

KLIXON® Tiny Stat™ 4BT Series Thermostats

### FEATURES

- Tiny Stat™ precision thermostat
- Smallest snap-acting thermal switches on the market
- Preset temperature set points
- Single pole, single throw (SPST)
- Hermetically sealed and back-filled with nitrogen
- Qualified to MIL-PRF-24236/13



### PERFORMANCE CHARACTERISTICS - 4BTD2-24

|                              |  |   |   |
|------------------------------|--|---|---|
| <b>Operating Temperature</b> | 46,1°C (115°F)   | <b>Differential</b>                       | 17°C (30°F)   |
| <b>Contact Operation</b>     | Close on rise  | <b>Tolerance</b>                          | +/- 4.4°C (8°F)   |
| <b>Contact</b>               | gold   | <b>Weight</b>                             | 0,2 grams   |
| <b>Wires</b>                 | No   |   |   |
| <b>Contact Ratings</b>       | <i>Cycles</i><br>10000<br>10000  | <i>Voltage</i><br>30 VAC / VDC<br>115 VAC | <i>Amps (resistive)</i><br>500 mA and below<br>200 mA and below |
| <b>Contact Resistance</b>    | 0.050 ohms maximum per MIL-STD-202, Method 307                                       |   |   |
| <b>Dielectric Strength</b>   | 500 Vac, RMS, 60 Hz for 5 seconds, across open contacts, per MIL-STD-202, Method 301 |   |   |
| <b>Vibration Resistance</b>  | 5–2000 Hz, 30 G, per MIL-STD-202, Method 204   |   |   |
| <b>Shock Resistance</b>      | 100 G, 6 milliseconds per MIL-STD-202, Method 213                                    |   |   |
| <b>Hermeticity</b>           | 1 x 10 <sup>-8</sup> atm cc/sec. maximum, per MIL-STD-202, Method 112, Condition C   |   |   |
| <b>Salt Spray Resistance</b> | Per MIL-STD-202, Method 101, Condition B, 5% solution                                |   |   |

### CONFIGURATION : Grounded Case Construction



[REQUEST QUOTATION](#)